

BRS-210

REFRIGERATED BASES

REFRIGERATED BASES

Refrigerated stand with 4 doors
Incorporated condensing unit -
Temperature: -2°C $+8^{\circ}\text{C}$ - 4 grids GN-1/1 -
340 lt. Refrigerant gas R290



Construction - Fabricated using CrNi 18/10 AISI 304 grade Stainless Steel Scotch-Brite Satin polish Finish, rounded edges and chromed details.
Model - Refrigerated stand with doors and drawers, for professional use.
Condensing unit incorporated, Refrigerant Gas R290. Automatic electric defrosting. Insulation with foam without CFC and HCFC. Fittings -
Appliance is supplied with adjustable feet.




ITALIAN CULINARY ART

The pictures are purely representative. The manufacturer reserves the right to modify the technical data and models without previous notice.

BRS-210

REFRIGERATED BASES

REFRIGERATED BASES



A	Data plate		B	Electrical connection	
---	------------	--	---	-----------------------	--

MODEL: BRS-210
DIMENSIONS: cm. 210x 63x 59h
ELECTRIC POWER: 0,37 kW
VOLTAGE: 230V~
FREQUENCY: 50 Hz



kg: 150
m³: 1.314
mm: 2250x730x800

BUY LOTUS BUY ITALY

The pictures are purely representative. The manufacturer reserves the right to modify the technical data and models without previous notice.



LOTUS S.P.A. Via Calmaor, 46
 31020 San Vendemiano(TV) - Italy
 Tel. + 39 0438 778020 / 778468
 Fax + 39 0438 778277
www.lotuscookers.it - lotus@lotuscookers.it