FTLR-912G

90 IPERLOTUS
GAS GRDDLE

View 3D

Gas Fry-top 1/3 grooved + 2/3 smooth, on open cabinet, plate cm.110,5x65 - 3 cooking areas (included 1 Head end filler strip mod.TPA-9)

Construction - Fabricated using CrNi 18/10 AISI 304 grade Stainless Steel Scotch-Brite Satin polish Finish, incorporating 2mm thick worktop, rounded edges, chromed details and rear splash back. Knobs with waterproof grades IPX5. Model - Professional Gas Griddle, Smooth, Ribbed or 50 / 50, Normal or Chrome, on open cabinet. Normal Plate in FE430B Steel and Chrome in FE510C Steel. Normal or Chrome plate in chrome-molibdeno, 20mm thick, for model FT-912/916. High durability and rapid heat up. Burners with Piezoelectric ignition and pilot light, 50 - 300degC control, thermostatic and thermocouple safety valves, Removable liquid containers. Maintenance - All serviceable parts are accessible by the easy removal of front control panel. Fittings - Appliance is supplied with both LPG and Natural Gas conversion jets and adjustable feet. Doors not included.



ITALIAN CULINARY ART

The pictures are purely representative. The manufacturer reserves the right to modify the technical data and models without previous notice.

FTLR-912G

90 IPERLOTUS
GAS GRDDLE

View 3D



A	Data plate		C	Gas connection	ISO 7-1 1/2" M

MODEL:	FTLR-912G
DIMENSIONS:	cm. 120x 90x 90h
GAS POWER:	27 kW / 23.220 kcal/h
GAS TYPE:	Natural Gas / LPG

kg:	198
m^3:	1.324
mm:	123x97x111

BUY LOTUS BUY ITALY

The pictures are purely representative. The manufacturer reserves the right to modify the technical data and models without previous notice.

LOTUS S.P.A.Via Calmaor, 46
31020 San Vendemiano(TV) - Italy
Tel. + 39 0438 778020 / 778468
Fax + 39 0438 778277
www.lotuscookers.it - lotus@lotuscookers.it